



BS EN 14351-1:2006+A1:2010

**WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS**

DECLARATION OF PERFORMANCE

THIS IS TO CERTIFY THAT

STEVLY LIMITED

of

Units E & F

Bowen Industrial Estate

Aberbargoed

Bargoed

CF81 9EP

HAVE CONFORMED WITH EN 14351-1:A1:2010 ANNEX ZA

FOR

VERTICAL SIDING & CASEMENT WINDOWS AND DOORS INTENDED TO BE USED IN DOMESTIC AND
COMMERCIAL LOCATIONS

INSTIGATING AND IMPLEMENTING A SYSTEM OF FACTORY PRODUCTION CONTROL COMPLYING
WITH EN 14351-1:A1:2010 ANNEX ZA

PRODUCING A TECHNICAL FILE CONTAINING THE TEST REPORT AND PERFORMANCE INDICATION
PAPERS FOR ALL COMPONENTS

INCLUDING THE FOLLOWING MANDATORY REQUIREMENTS

LOAD BEARING CAPACITY OF SAFETY DEVICES - Clause 4.8

THERMAL CHARACTERISTICS - Clause 4.12

DANGEROUS SUBSTANCES - Clause 4.6

Signed: ...Lee Johnson.....

Date: ...24/6/13.....

Position: ...Director.....



STEVLY LIMITED

of

Units E & F

Bowen Industrial Estate

Aberbargoed

Bargoed

CF81 9EP

13

EN 14351-1:A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

System: PVCu or Timber Windows and Doors

<u>Characteristics</u>	Declared Value
Dangerous Substances	None
Thermal Transmittance	$\leq 3.2W/(m^2K)$
Load Bearing Capacity of Safety Devices	Passed
Resistance to Wind Load	npd
Resistance to snow and permanent load	npd
Reaction to fire	npd
External Fire Performance	npd
Water tightness	npd
Impact Resistance	npd
Radiation Properties	npd
Acoustic Performance	npd
Air Permeability	npd

This declaration relates to a worst case scenario and as such all our products will give an equal to or better (lower) than performance to that quoted

Signed:.....

Position:.....

Date:.....



STEVLY LIMITED

of

Units E & F

Bowen Industrial Estate

Aberbargoed

Bargoed

CF81 9EP

13

EN 14351-1:A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

System: Metal Windows and Doors with no thermal break

<u>Characteristics</u>	Declared Value
Dangerous Substances	None
Thermal Transmittance	$\leq 4.1W/(m^2K)$
Load Bearing Capacity of Safety Devices	Passed
Resistance to Wind Load	npd
Resistance to snow and permanent load	npd
Reaction to fire	npd
External Fire Performance	npd
Water tightness	npd
Impact Resistance	npd
Radiation Properties	npd
Acoustic Performance	npd
Air Permeability	npd

This declaration relates to a worst case scenario and as such all our products will give an equal to or better (lower) than performance to that quoted

Signed:.....

Position:.....

Date:.....